

Options and Accessories



Lighting Package*



Turn Signals



One-Piece Windshield



Fold-Down Windshield



West Coast Mirror/
Heavy-Duty Bumper



Glove Box
With Lock



Cargo Box



Stake-Side Kit



Fold-Down Seat



3-Sided Enclosure



Heavy-Duty
Batteries



Hour Meter



Extra-Traction Tires



Communication
Display Module



Wheel Covers



Canopy Top
White and Beige



5-Panel Mirror

*Headlights, Taillights,
Brakelights and Horn



Ingersoll Rand is a world leader in the field of compact vehicles and equipment. Our widely known Bobcat® brand includes an extensive line of powerful, nimble compact construction equipment and attachments, and our state-of-the-art engineering capabilities and stylish designs are reflected in our world famous Club Car® vehicles.

1.800.ClubCar • +1 706.863.3000

www.clubcar.com www.bobcat.com www.ingersollrand.com

CCN 18033118 Rev 08/06

Club Car®

Villager 6

TRANSPORTATION VEHICLE



Villager 6

Stylish. With uncompromising comfort, convenience and terrific handling. The Villager 6 increases your passenger capacity. Offering more transportation capability virtually anywhere. From airports to industrial facilities to resorts to amusement parks. Chauffeur up to



6 people easily and reliably while offering an enjoyable experience.

Features

Club Car's exclusive IQ Plus System™ electric or 11.5 hp gas engine



Fixed rear seat (fold-down seat available)



Rugged, rustproof aluminum frame, and chassis



Molded, seamless vinyl seats



Self-adjusting, maintenance-free rack & pinion steering




ArmorFlex® fade-resistant front body



Standard Color: White



Optional Colors: Beige, Gray, Dark Gray, Green, Classic Blue, Red, Black and Burgundy



6-ply, premium tread tires



Smooth, independent front and semi-independent rear suspension



Additional Features

- Maximum speed of 17 mph (27.3 kph) (Electric vehicles only)
- 1,500 lb (681 kg) total vehicle capacity
- Seating for six
- Maximum hp @ 3,600 rpm exceeds SAE J1940 Performance Standards
- Headlights, taillights, brakelights and horn
- 48-volt IQ Plus electric motor or 351 cc, 11.5 hp gas, pedal-start engine
- 4-wheel brakes

Specifications

	Villager 6 Electric with exclusive IQ Plus System	Villager 6 Gasoline	
POWER SUPPLY	Engine	N/A	Kawasaki 4-cycle, OHV, 351 cc, single cylinder, air-cooled, pressure-lubricated, spin-on oil filter
	Drive Motor	48-volt Shunt/Sepex	N/A
	Horsepower	3.7 @ 3400 rpm (continuous) 21.0 @ 2000 rpm (peak)	11.5**
	Governor	N/A	Automatic ground speed sensing, Internally geared-in unitized transaxle
	Governed RPM	N/A	3050 +/- 30
	Ignition	N/A	Electronic w/electronic RPM limiter
	Drive Unit	12.3:1 direct-drive axle, double reduction helical gear	Unitized Transaxle, helical gears: 11.8:1 forward, 17.1:1 reverse
	Electrical System	48-volt	12-volt, 500 cca 105 min. reserve
	Batteries	Eight 6-volt, Standard: T105 = 115 min @ 75 amps; Heavy Duty: T145 = 145 min @ 75 amps	N/A
	Charger	Automatic, computer-controlled 48-volt DC, 17 amp, UL and CUL listed; international CE marked available	N/A
Controller	500 amp Solid State	N/A	
STEERING/ SUSPENSION	Steering	Self-adjusting rack & pinion	Self-adjusting rack & pinion
	Front Suspension	Independent leaf spring with dual hydraulic shocks	Independent leaf spring with dual hydraulic shocks
	Rear Suspension	Leaf springs with dual hydraulic shocks	Leaf springs with dual hydraulic shocks
	Brakes	Four Wheel Mechanical Drum	Four Wheel Mechanical Drum
	Park Brake	Foot-operated, multi-lock	Foot-operated, multi-lock
	Stabilizer Bar	No	Yes
FRAME/CHASSIS	Frame/Chassis	Aluminum I-Beam	Aluminum I-Beam
	Front Body	ArmorFlex®	ArmorFlex®
	Rear Body	ArmorFlex®	ArmorFlex®
	Body Finish	Matching paint over molded in color	Matching paint over molded in color
	Light Package	Std. Light Package	Std. Light Package
	Front Tires	18 x 8.50-8, 6-ply rated, Premium tread	18 x 8.50-8, 6-ply rated, Premium tread
	Rear Tires	18 x 8.50-8, 6-ply rated, Premium tread	18 x 8.50-8, 6-ply rated, Premium tread
	Instrumentation	Battery capacity indicator, battery warning light	Electronic fuel gauge/hour meter, Low-oil warning light
DIMENSIONS	Total Vehicle Capacity	1500 lb. (681 kg)	1500 lb. (681 kg)
	Overall Length	124" (315 cm)	124" (315 cm)
	Overall Width	47.3" (120.1 cm)	47.3" (120.1 cm)
	Overall Height	48" (121.9 cm)	48" (121.9 cm)
	Wheelbase	98.5" (250.2 cm)	98.5" (250.2 cm)
	Ground Clearance Under Differential	4.5" (11.4 cm)	4.5" (11.4 cm)
	Fuel Tank Capacity	N/A	7 gallons (26.5 liters)
	Tread	34.5"/38.5" (87.6 cm/97.8 cm)	34.5"/38.5" (87.6 cm/97.8 cm)
	Dry Weight Less Batteries	590 lb. (267.9 kg)	745 lb. (338.2 kg)
	Speed Range	5 - 17 mph (8-27.3 kph)	14 - 16 mph (22.5-25.7 kph)
	Outside Clearance Circle	24.7 ft. (7.5 m) dia.	24.7 ft. (7.5 m) dia.
	Turning Radius	12 ft. (3.7 m)	12 ft. (3.7 m)
	Intersecting Aisle Radius	90" (228.6 cm)	90" (228.6 cm)
Vehicle Warranty	2-year, limited/4-year batteries*	2-year, limited	

*4-year, limited battery warranty for electric vehicles
**Maximum hp @ 3,600 exceeds SAE J1940 Performance Standards

